ANEMOMETER

Model: SP-82AM *ISO-9001, CE, IEC1010*









2 in 1, Air velocity, Air flow

ANEMOMETER

Model: SP-82AM

FEATURES

- * 2 in 1 professional environment instruments:
 - 1. Air velocty/Temp., 2. Air flow (CMM, CFM).
- * Tiny bone shape with lightweight and small size case design are suitable for handling with one hand.
- * Wristlet design provides extra protection to the instrument especially for user one hand operation.
- * Low-friction ball bearing mounted wheel design provides high accuracy at high and low air velocity.
- * Built- in microprocessor circuit assures excellent performance and accuracy.
- * Concise and compact buttons arrangement, easy operation.
- * Memorize the maximum and minimum value with recall.
- * Hold function to freeze the current reading value.

GENERAL SPECIFICATIONS				
Display	8 mm LCD display			
Measurement	1. Air velocty/Temp.			
	2. Air flow (CMM, CFM).			
Operating	Max. 80% RH.			
Humidity				
Operating	0 to 50 ℃ (32 to 122 °F)			
Temperature				
Over Input	Indication of " "			
Display				
Power Supply	CR 2032 DC 3V battery			
Power	Approx. DC 5 mA			
Consumption				
Weight	160g (battery included)			
Dimension	HWD 120 x 45 x 20 mm (4.7 x 1.8 x 1.2 inch).			
Standard	Instruction Manual			
Accessory				

ELECTRICAL SPECIFICATION (23 ± 5°C)				
Air velocity	/	•	•	
Unit	Range	Resolution	Accuracy	
ft/min	80 to 3937 ft/min	1 ft/min		
m/s	0.4 to 20.0 m/s	0.1 m/s	\leq 20 m/s : ± 3% F.S.	
km/h	1.4 to 72.0 km/h	0.1 km/h	> 20 m/s : ± 4% F.S.	
MPH	0.9 to 44.7 mile/h	0.1 MPH		
knots	0.8 to 38.8 knots	0.1 knots		
Temp.	0 to 50 ℃	0.1 ℃		
	32 to 122 °F	0.1 °F		

Remark :

ft/min : feet per minute MPH : miles per hour

m/s: meters per second knots: nautical miles per hour

km/h : kilometers per hour

Ar flow				
Unit	Range	Resolution		
CMM	0.024 to 36000	0.001/0.01/0.1/1		
CFM	0.847 to 1271300	0.001/0.01/0.1/1/10 (x10)/100 (x100)		

^{*} Appearance and specifications listed in this brochure are subject to change without notice.